



BK-FD50S



BK-FD50T



BK-FD100S



BK-FD100T

TECHNICAL PARAMETERS

BK-FD50S(Standard)		BK-FD50T(Stoppering)		BK-FD100S(Standard)		BK-FD100T(Stoppering)	
0.5m ²				1m ²			
-50℃~+70℃							
-80℃							
<10Pa				<10Pa			
7.5kg				15kg			
18L				35L			
Φ255*350mm				Φ300*500mm			
470*548*550mm				640*685*550mm			
Shelf: 305*455*17mm				Shelf: 550*480*17mm			
Tray: 300*450*20mm				Tray: 475*272*25mm			
Shelf: 4+1, Tray: 4		Shelf: 3+1, Tray: 3		Shelf: 6+1, Tray: 6		Shelf: 4+1, Tray: 4	
5L				10L			
90mm							
±1℃							
R404A + R23							
Air cooling							
Electric defrosting							
/	Hydraulic			/	Hydraulic		
1040				2016			
1944				3944			
3456				7020			
8L/S(29m ³ /h)				15L/S(54m ³ /h)			
500W				600W			
800W				1600W			
/	1.5KW			/	1.5KW		
7KW	8.5KW			8.5KW	10KW		
AC220V, 50/60Hz(single phase); AC380V, 50/60Hz(three phase)				AC380V, 50/60Hz(three phase)			
AC220V, 50/60Hz(three phase)				AC220V, 50/60Hz(three phase)			
470kg				730kg			
1200*850*1500/1850				1500*1000*1600/1950			
1250*900*1560 / 472kg	1250*900*1880 / 520kg			1700*1120*1800 / 650kg	1700*1120*1960 / 750kg		
715*280*315 / 65kg				715*280*315 / 85kg			